



W563mm 16" H716mm D(see table) Suitable for:

Slimline Radiant* Deepline Radiant* Mid-Depth H.E

Deepline H.E Balanced Flue



Fire Engine	Slimline Radiant*	Deepline Radiant*	Mid-Depth HE	Deepline HE	Balanced Flue
Trim (mm)	W:563mm H:716mm	W:563mm H:716mm	W:563mm H:716mm	W:563mm H:716mm	W:563mm H:716mm
Inset (mm)	W:403mm H:553mm D:123mm	W:403mm H:553mm D:173mm	W:403mm H:553mm D:128mm	W:403mm H:553mm D:198mm	W:400mm H:550mm D:186mm
Open / Glass Fronted	Open Fronted	Open Fronted	Glass Fronted	Glass Fronted	Glass Fronted
Xtra Canopy	\checkmark	\checkmark	\boxtimes	\boxtimes	\boxtimes
Min Aperture in Chimney	W:405mm H:555mm	W:405mm H:555mm	W:405mm H:555mm	W:405mm H:555mm	N/A
EEC	F	F	D	С	С
Efficiency	52% (58% with Xtra Canopy)	52% (55% with Xtra Canopy)	82%	87%	86%
Install in	Pre-Cast / Pre-Fab / Brick Chimney	Pre-Cast* / Pre-Fab / Brick Chimney	Pre-Cast / Pre-Fab / Brick Chimney	Pre-Fab / Brick Chimney	Balanced Flue
Control	Smartslide / Manual	Smartslide / Manual	Smartslide	Smartslide	Smartslide / Manual

^{*}When installed with a 75mm rebate surround

Contact us

Elgin & Hall





















